

# Chequer Plate Dura

Chequer Plate Dura Rubber Mat is a low-cost surface covering, recommended for applications where safety and slip protection are crucial but without the need for anti-fatigue properties. The diamond-embossed chequer plate surface provides exceptional non-directional grip, making it suitable for workbenches as well as flooring.

## Features

- **Typical applications:** Perfect for warehouse aisles, industrial walkways, as shelf liners, on workbenches and near machines to prevent objects sliding.
- **Material:** 100% rubber.
- **Cleaning:** Wash with cold water, use a vacuum cleaner, or a pressure pump to remove dirt. The use of harsh detergents is not recommended.
- **Sustainability:** Nature friendly, biodegradable and recyclable. REACH compliant. Contributes to a cleaner environment by reducing the need to use cleaning chemicals.
- **Warranty:** Lifetime.



Suitable for indoor use



Code	Metric	Imperial	Thickness	Weight	Type	Colour
06-0347	120cm x 10m	4' x 33'	3mm	35kg	Roll	Black

Please note, all Imperial sizes have either been rounded up or down to the nearest whole number

# Chequer Plate Dura

## Technical Specification

Slip resistant:	Great slip resistance to level 2
Anti-fatigue:	Good anti-fatigue properties, resistant to level 1
Wear resistant:	Excellent wear resistance to level 3, suitable for heavy footfall
Cut to length:	Yes, mat can be cut to length
Cut to size:	Yes, mat can be cut to bespoke sizes
Disability friendly:	Yes, the low profile makes it suitable for wheelchair users
Dry area:	Yes
Wheeled area:	Yes, the low profile allows easy access for wheeled traffic
Environment:	Suitable for indoor use
Impact resistant:	Yes
Product testing:	<ul style="list-style-type: none"> <li>▪ Hardness: 85+/-5 shore A - DIN ISO 7619-1</li> <li>▪ Volume weight: 1.82g/cm<sup>3</sup> - DIN 53504</li> <li>▪ Tensile strength: Direction 1 - 1690psi/direction 2 - 1940psi ASTM D412-16</li> <li>▪ Elongation at break: 190% - ASTM D3574-17 Test E</li> <li>▪ Puncture resistance - EN388:2016+A1:2028, Clause 6.5</li> <li>▪ Indentation resistance - ASTM F970-17</li> </ul>
Sustainability:	<ul style="list-style-type: none"> <li>▪ Nature friendly, biodegradable and recyclable</li> <li>▪ REACH (Registration, Evaluation, Authorisation and Restrictions of Chemicals)</li> <li>▪ Contributes to a cleaner environment by reducing the need to use cleaning chemicals</li> </ul>
Cleaning:	Wash with cold water, use a vacuum cleaner, or a pressure pump to remove dirt. The use of harsh detergents is not recommended