

## **TreadSure**

TreadSure is a low cost, surface covering suitable for use in a wide variety of applications. The ribbed surface provides excellent grip for both floor surfaces and work areas alike. It is easy to cut and can be laid loose or glued/ fixed down for a more permanent solution. Available in two different thicknesses, 3mm and 6mm, TreadSure is suitable for medium to heavy duty use.

## **Features**

- Typical applications: Low-cost surface covering, suitable for industrial flooring, aisles, work benches, vehicle interiors, kennels, livery enclosures and animal grooming areas.
- Material: 100% rubber.
- Cleaning: Wash with cold water, use a vacuum cleaner, or a pressure pump to remove dirt. The use of harsh detergents is not recommended.
- Sustainability: REACH compliant. Contributes to a cleaner environment by reducing the need to use cleaning chemicals.



• Warranty: Lifetime.



Code	Metric	Imperial	Thickness	Weight	Туре	Colour
06-0335-1	90cm x 10m	3' x 33'	3mm	26.1kg	Roll	Black
06-0335-3	90cm x 10m	3' x 33'	6mm	76kg	Roll	Black
06-0335-4	100cm x 10m	3' x 33'	6mm	83kg	Roll	Black
06-0335-2	120cm x 10m	4' x 33'	3mm	35kg	Roll	Black
06-0335-5	120cm x 10m	4' x 33'	6mm	97kg	Roll	Black

Please note, the width and length can be +/- 2%

Please note, all Imperial sizes have either been rounded up or down to the nearest whole number





## TreadSure

Technical Specification					
Slip resistant:	Great slip resistance to level 2				
Anti-fatigue:	Good anti-fatigue properties, resistant to level 1				
Wear resistant:	Great wear resistance to level 2, suitable for medium to high footfall				
Cut to length:	Yes, mat can be cut to length				
Cut to size:	Yes, mat can be cut to bespoke sizes				
Disability friendly:	Yes, the low profile makes it suitable for wheelchair users				
Dry area:	Yes				
Wheeled area:	Yes, the low profile allows easy access for light weight wheeled traffic				
Environment:	Suitable for indoor and outdoor use				
Impact resistant:	Yes				
Product testing:	<ul> <li>Hardness Shore A ±5 65° ISO 7619-1</li> <li>SG (g/cm<sup>2</sup>) 1.50 ISO 2781</li> <li>Tensile (N/mm<sup>2</sup>) 2.5 ISO 37</li> <li>Elongation % 200 ISO 37</li> </ul>				
Sustainability:	<ul> <li>REACH (Registration, Evaluation, Authorisation and Restrictions of Chemicals)</li> <li>Contributes to a cleaner environment by reducing the need to use cleaning chemicals</li> </ul>				
Cleaning:	Wash with cold water, use a vacuum cleaner, or a pressure pump to remove dirt. The use of harsh detergents is not recommended				